



# License No. 896 to mark a commodity with the Standards Mark

The Standards Institution of Israel (SII), in accordance with the powers vested in it by article 11(b) of the Standards law 1953, hereby grants permission to:

**YTONG LTD. - PARDES HANA PLANT**

**MEMBER OF YTONG INDUSTRIES**

Park Inds. Kesaria, P.O.B 1017 ,Pardes Hana ,Israel

to place the Standards Mark on the commodities covered by the standard:  
**Autoclaved Aeraed - Concrete Blocks**

(list of types attached)

**These commodities are produced in conformity with the requirements of the  
Israel Standard No. 268 Edition March 2017 Amendment 1**

This license has been granted subject to the terms of the Standards Regulation (standard mark and supervision sign) 1982, and the terms that the License Committee has determined, which constitute an integral part of this license. This license does not detract from any obligation, or other order, imposed by law on the abovementioned commodities

This certificate remains the property of SII. Its continued validity may be verified via scanning the barcode or via the SII website [www.sii.org.il](http://www.sii.org.il).

**This license is valid until 31/12/2024**

Date of License : 26/12/2023



R.N 511212615

Dr. Gilad Golub  
CEO



The standards Institution of Israel  
42 Chaim Levanon St,  
Tel-Aviv 6997701



## Annex A: License No. 896

**Factory: YTONG LTD. - PARDES HANA PLANT MEMBER OF YTONG INDUSTRIES**

**Commodities: Autoclaved Aeraed - Concrete Blocks**

### Models:

1. Product name: "Ytong for Ceiling"  
Product name: "Ytong isolation panel EXTRA"  
Dimensional tolerances: GPLM, Mean compressive strength 1.0 Mpa. Dry density: 280 kg/m<sup>3</sup>  
Dry Thermal conductivity (LAMBDA 10):0.074
2. Product name: "Ytong for Building"  
Product name: "Ytong for Partitions"  
Dimensional tolerances: GPLM, Mean compressive strength 2.5Mpa Dry density: 400 kg/m<sup>3</sup>.  
Dry Thermal conductivity (LAMBDA 10):0.109
3. Product name: "Ytong for bearing construction"  
Product : "Ytong for covering stone with adhesion"  
Dimensional tolerances: GPLM, Mean compressive strength 4.0 Mpa. Dry density: 580 kg/m<sup>3</sup>  
Dry Thermal conductivity (LAMBDA 10):0.152
4. Product name: "Ytong Acoustic"  
Dimensional tolerances: GPLM, Mean compressive strength 4.3 Mpa. Minimum dry density: 650 kg/m<sup>3</sup>

**This license is valid until 31/12/2024**

Date of License : 26/12/2023



R.N 511212615

Dr. Gilad Golub  
CEO